

SUPAFLEX

BLAST HOSE



APPLICATIONS

Particularly abrasion resistant softwall hose, used for the delivery of garnet or cast steel shot. It is manufactured with an antistatic rubber compound that prevents the risk of static electricity.

CERTIFICATIONS, RATINGS AND STANDARDS

Abrasion resistance of the hose according to:

ISO 4649:2010, 50 +/- 5mm³.

Standard/Approval: Exceeds ENISO 3861:2008

Temperature Range: -35°C to +80°C

CONSTRUCTION

Tube: Black, smooth, antistatic SBR/NR rubber, abrasion resistant.

Cover: Black, smooth, (wrapped finish) antistatic SBR/NR rubber abrasion resistant.

Reinforcement: High strength synthetic cord.

PART NUMBERS	
BHS1350	12.5mm (1/2") ID 50'
BHS2050	20mm (3/4") ID 50'
BHS2550	25mm (1") ID 50'
BHS3250	32mm (1-1/4") ID 50'
BHS32100	32mm (1-1/4") ID 100'
BHS4050	38mm (1-1/2") ID 50'
BHS40100	38mm (1-1/2") ID 100'

Part No.	Inside Diameter		Outside Diameter		Safety Factor	Weight Nominal		Length Max	
	mm	inches	mm	inches	bar	kg/m	lbs/ft	m	ft
BHS1350	12.5	0.50	30	1.18	3:1	0.40	0.27	120	400
BHS2050	20	0.75	34	1.34	3:1	0.60	0.40	120	400
BHS2550	25	1.00	40	1.57	3:1	0.84	0.56	120	400
BHS3250	32	1.25	48	1.89	3:1	1.10	0.74	120	400
BHS4050	38	1.5	55	2.16	3:1	1.63	1.10	120	400