

SCHMIDT AMPHIBLAST LITE

DESCRIPTION

The Schmidt AmphiBlast™ Lite 3.5 is simple, portable and accurate. It gives the operator the option of blasting wet, dry, Softwash™ or blowdown with repeatable and optimal flow parameters for each function.

Minimal water usage (less than 1 pint/ ½ liter) with proprietary Schmidt M.I.S.T.™ technology that allows precise control of the amount of water injected into the air stream while blasting.

KEY FEATURES

- Wet blast or dry blast with a single unit
- Minimal water usage (less than 1 pint / ½ litre per minute) with proprietary Schmidt M.I.S.T.™ technology that allows precise control of the amount of water injected into the air stream while blasting
- Set and forget switching between machine modes
- Abrasive tank is “dry” so there is no need to drain water to refill with abrasive. This creates a significantly cleaner job site and is more efficient
- Industry-leading productivity and reliability from Schmidt abrasive blasting technology
- Schmidt TeraValve™ XL abrasive metering valve offers precise and repeatable control of a wide range of coarse or fine abrasives
- Wide range of blasting pressure capabilities from 10 to 150 psi
- Toggle between wet blast, dry blast, and blow-off using a single control panel
- Increased portability



PART NUMBER	
BM SAMPFIL35	AmphiBlast Lite
SPECIFICATIONS	
Dimensions (L,W,H)	33" x 23" x 53"
Weight	270 lbs (empty)
Blast Pot	3.5 cu. ft