

COPPERVAC

VACUUM HOSE

DESCRIPTION

Heavy duty, extra thick abrasion resistant polyurethane liner with rigid PVC spiral reinforcing. Copper wire wrapped for enhanced static dissipation.

APPLICATIONS

Highly abrasion-resistant polyurethane-lined Material Handling Vacuum Hose, used for the recovery of abrasive media. Also suitable for general applications where abrasion resistance is required, such as gravel and sand vacuuming.

FEATURES

- Heavy duty, extra thick abrasion resistant liner
- Rigid PVC spiral for reinforcement
- Flexible, even in cold temperatures
- Copper wire, for static dissipation



SPECIFICATIONS						
Part Number	ID (inches)	Length (ft)	Min. Bend radius (ft)	Working Pressure (psi)	Vacuum rating (in HG)	Weight
AHCVP05050	2	50	5.5	29	26	0.72 lb/ft (1 kg/m)
AHCVP050100	2	100	5.5	29	26	0.72 lb/ft (1 kg/m)
AHCVP07550	3	50	7.5	29	26	1.10 lb/ft (1.63 kg/m)
AHCVP075100	3	100	7.5	29	26	1.10 lb/ft (1.63 kg/m)
AHCVP10050	4	50	11	29	26	1.83 lb/ft (2.72 kg/m)
AHCVP100100	4	100	11	29	26	1.83 lb/ft (2.72 kg/m)
AHCVP15050	6	50	20	15	23	2.9 lb/ft (4.31 kg/m)
AHCVP150100	6	100	20	15	23	2.9 lb/ft (4.31 kg/m)
AHCVP20025	8	25	30	15	23	4.5 lb/ft (6.71 kg/m)
AHCVP20050	8	50	30	15	23	4.5 lb/ft (6.71 kg/m)

CopperVac hose. Designed to Last Longer. Much Longer.