

ENVIRO PREP® PREMIUM



DESCRIPTION

Enviro-Prep® Premium is a water-borne, pH neutral coating used to abate hazardous lead-based paint during its removal from an assortment of substrates. The Enviro-Prep System® converts lead to a highly insoluble inorganic compound, creating non-hazardous waste which is stable for disposal in a regular landfill. The product is applied to a leaded surface and then removed by any common removal method.

APPLICATIONS

- Asphalt
- Bridges
- Concrete
- Heavy Equipment
- Ship Platforms
- Storage tanks
- Structural Steel
- Subway/Rail Stations
- Warehouses
- Water Towers
- Light Poles
- Old Housing

CERTIFICATIONS AND RATINGS

pH Level:	7.0 – 8.0
Spreading Rate:	@ 5 wet mils – 350 sq ft/gal @ 10 wet mils – 175-190 sq ft/gal @ 15 wet mils – 115-130 sq ft/gal @ 20 wet mils – 85-100 sq ft/gal
Specific Gravity:	Shot blasting
VOC:	0.07 lb/gal

*Dry times may vary depending on temperature, humidity and degree of air movement.

B3036-2

VOC (less water):	0.31 lb/gal
Dry Time:	77°F at 50% R.H.
To Touch:	2-3 Hours can be blasted while still wet to cut down on dusting.

This product should be applied at a recommended thickness for the generated waste to pass the Toxicity Characteristic leaching Procedure (TCLP) test. If frozen, must be thawed and agitated before use.

EQUIPMENT

This product can be applied by conventional, HVLP, and airless spray equipment. Recommended settings depend on the equipment make and model. When using spray equipment, recommended tip size is 19 and over – remove all filters.

REDUCTION

No reduction is necessary. This product is intended for use as packaged.

SURFACE PREPARATION

No surface preparation is required.

CHARACTERISTICS

- Ease of application
- Long term stability
- Low dusting during blasting
- Passes both TCLP and Synthetic Precipitation Leaching Procedure (SPLP) testing when used at recommended dosage
- Proven history
- Use any removal method