

REINFORCED SCAFFOLD SHEETING

DESCRIPTION

Premium poly sheeting designed for projects requiring 100% containment. Easy to install using specially designed bungees (available separately). Doubly reinforced with string throughout and also with eyelet bands where the bungees are used.

APPLICATIONS

While the primary application is for abatement/ environmental enclosures where 100% containment is required, it can also be used for total weather protection (including enclosing temporary heat), restoration & construction enclosures, and general dust/debris/demolition control.



FEATURES

- 6 or 12 mil thickness
- FR or non-FR available
- Reinforced blue bands with eyelet holes for fastening bungee ties
- Water, mildew and tear resistant
- Stays flexible in cold weather

ITEM SPECIFICATIONS

Part Number	Rating	Color	Width	Length	Thickness	Weight	Pallet Qty
PCSL620100-FR	FR	White	20	100	6 mil	46 lbs	24 rolls
PCSL620100-NFR	Non-FR	Clear	20	100	6 mil	46 lbs	24 rolls
PCSL1274136-FR	FR	White	7'4"	136	12 mil	60 lbs	24 rolls
PCSL1274136-NFR	Non-FR	Clear	7'4"	136	12 mil	60 lbs	24 rolls
PCSL1286100-FR	FR	White	8'6"	100	12 mil	49 lbs	25 rolls
PCSL1213100-FR	FR	White	13	100	12 mil	74 lbs	20 rolls
PCSL1213100-NFR	Non-FR	Clear	13	100	12 mil	74 lbs	20 rolls
PCSL1220100-FR	FR	White	20	100	12 mil	110 lbs	12 rolls
PCSL1220100-NFR	Non-FR	Clear	20	100	12 mil	110 lbs	12 rolls