BLASTONE
SUPERIOR PERFORMANCE

SNAKEBITE FLEX
BLAST NOZZLE

Low Pressure Silencer

Standard Silencer

DESCRIPTION

The SnakeBite Flex is a compact blast nozzle design, based on proven SnakeBite technology, that delivers up to 16dBA noise reduction and 45% lower nozzle thrust.

SnakeBite Flex – all the power – half the size.

APPLICATIONS

Best suited for use in tight, hard-to-reach spaces or where there is a requirement to blast in and around obstacles such as brackets or flanges, general structural steel or smaller beams or pipes.

FEATURES

- Compact size allows better access for tight spaces
- Improved blast nozzle geometry.
- Durable and lightweight Silicon Nitride Nozzle and Silencer liners.
- Slimline ergonomic nozzle jacket.
- Standard contractor nozzle inlet thread.
- Robust anodized aluminum nozzle jacket, including a nozzle exit bump guard.

BENEFITS

LOWER NOISE

- Enhanced ability to work during restricted quiet times
- Reduces risk of hearing damage to operators and bystanders

LOWER THRUST

- Reduces operator fatigue, increasing productivity over long shifts
- Enhances safety and quality by improving operator control of blast hose

ENHANCED CAPABILITY

- Now 2 versions, silencing at almost all common blasting pressures between 70-110psi

SPECIFICATIONS	
Nozzle Jacket Material	Anodized Aluminum
Nozzle Liner Material	Silicon Nitride
Nozzle Inlet Thread	Contractor
Working Pressure	Standard Silencer - 90-110psi | Low Pressure Silencer - 70-90psi

PART NUMBERS	
BNSBXQ1506LPS	SnakeBite XQ Blast Nozzle, 3/8" Orifice (#6) with Low Pressure Silencer
BNSBXQ1507LPS	SnakeBite XQ Blast Nozzle, 7/16" Orifice (#7) with Low Pressure Silencer
BNSBXQ1508LPS	SnakeBite XQ Blast Nozzle, 1/2" Orifice (#8) with Low Pressure Silencer
BNSBXQ1506	SnakeBite Flex Blast Nozzle, 3/8" Orifice (#6) with Standard Silencer
BNSBXQ1507	SnakeBite Flex Blast Nozzle, 7/16" Orifice (#7) with Standard Silencer
BNSBXQ1508	SnakeBite Flex Blast Nozzle, 1/2" Orifice (#8) with Standard Silencer

Nozzle Size	Minimum air hose size	Minimum blast hose size	Weight (with silencer)	Length (with silencer)
No. 6 (3/8)	2" (50 mm)	1-1/4" (32mm)	1.5 lb (0.7 kg)	9.1 in (230 mm)
No. 7 (7/16)	2" (50 mm)	1-1/4" (32mm)	1.6 lb (0.73 kg)	9.4 in (240 mm)
No. 8 (1/2)	2" (50 mm)	1-1/4" (32mm)	1.7 lb (0.77 kg)	10 in (254 mm)

B4860-2